



TAKAGI MFG. CO., LTD.
HEATING & COOLING SYSTEM
 MADE IN JAPAN



①	COLD SIDE (C1020) /COLD SOURCE
②	THERMAL INSULATING MATERIAL (VITON RUBBER)
③	HOT SIDE (C1020) /HEAT SOURCE
④	SEEBECK DEVICE (Bi-Te)

THERMOELECTRIC GENERATION MAX : 20 [W]
 HOT SIDE/HEAT SOURCE [°C] : SEEBECK DEVICE SURFACE 95 [°C]
 DO NOT EXCEED 205 [°C]
 COLD SIDE/COLD SOURCE [°C] : SEEBECK DEVICE SURFACE -15 [°C]
 COLD SOURCE/RECOMMENDED FLOW RATE : 2~5 [L/min]
 (LIQUID : WATER, ETHANOL, ETHYLENE GLYCOL & WATER
 TEMP. RANGE : -50~5 [°C], BEYOND THIS RANGE DETERIORATES
 PERFORMANCE)
 WEIGHT : ABOUT 6 [kg]
 SCALE : NOT TO SCALE (NTS)
 UNIT : mm
 PROJECTION : THIRD ANGLE PROJECTION METHOD
 DIMENSIONAL TOLERANCE : ±0.5

1. Performance data on drawings, catalogs, handling manuals, and our documentation is reference only, and is not guaranteed.
2. This product is designed by us. Production and copy of this product without our permission is not permitted.

TITLE	SEEBECK UNIT
USE FOR	(THERMOELECTRIC GENERATION MAX : 20 [W])
ITEM NUMBER	SU-50WW